# **CLARIOstar®**

The Microplate Reader Company

# High Performance Microplate Reader with Advanced LVF Monochromators<sup>TM</sup>





# Anything is Possible with the CLARIOstar®

Any Wavelength
Any Bandwidth
Any Assay

# Triple Technology

The CLARIOstar is a multimode, high-performance microplate reader with a revolutionary new type of dual monochromator technology. The advanced LVF Monochromators™, along with filters and a spectrometer, can be used for a variety of applications in the different detection modes.

The following three detection technologies guarantee that the CLARIOstar does not compromise on sensitivity or flexibility:

- □ LVF Monochromators offer the best flexibility
- Spectrometer provides the fastest spectra
- □ **Filters** ensure the greatest sensitivity

# Modular, Upgradable Microplate Reader

The CLARIOstar is a modular, upgradable microplate reader that can fit the current and future needs of all laboratories and core facilities. It performs all of the leading non-isotopic detection technologies, including:


- □ UV/Vis Absorbance
- □ Fluorescence Intensity, including FRET
- □ Fluorescence Polarization/Anisotropy
- □ Time-Resolved Fluorescence, including TR-FRET
- □ AlphaScreen®/AlphaLISA®
- Luminescence (flash and glow), including BRET



A linear variable long pass filter slide (shown) is one of many specialized components that make up the CLARIOstar's sophisticated LVF Monochromator system.

# LVF Monochromator™ Technology

With the CLARIOstar, BMG LABTECH introduces a revolutionary new type of dual monochromator technology for fluorescence and luminescence measurements. The LVF Monochromators are based on Linear Variable Filters, which have variable coatings along their lengths that can reject or pass certain wavelengths of light. A linear variable filter consists of two slides, a linear variable long pass and a linear variable short pass, that when properly aligned separate light into distinct wavelengths and continuously adjustable bandwidths.‡



Simplified schematic of the CLARIOstar's LVF Monochromator.

The CLARIOstar contains two LVF Monochromators, one for excitation and one for emission. In addition, a linear variable dichroic mirror (340 - 740 nm) separates the two LVF Monochromators.

#### **Greater Sensitivity**

Since LVF Monochromators separate light differently than conventional monochromators, they provide significantly higher sensitivity for several reasons:

#### No stray light

The LVF Monochromator design avoids stray light that occurs with conventional monochromators. Avoiding stray light decreases the background signal and significantly increases sensitivity.

#### □ More light with adjustable bandwidths up to 100 nm

The LVF Monochromators have continuously adjustable bandwidths from 8 to 100 nm, which is unique. Larger bandwidths allow more light for excitation and emission, which means greater sensitivity.

#### □ Less background signal with a Linear Variable Dichroic


The linear variable dichroic mirror separates the excitation from the emission light. This greatly reduces the background signal.

# **Greater Flexibility**

Top and bottom reading for fluorescence and luminescence assays can be done with monochromators or filters. The CLARIOstar's inline optical system can also combine a monochromator with a filter. For instance, an excitation filter can be used with the emission LVF Monochromator. This gives the CLARIOstar unsurpassed flexibility for your research.

#### **Superior Spectral Scanning**

Spectral scanning is possible in both fluorescence and luminescence modes with the LVF Monochromators. Whether developing an assay with a new fluorophore or modifying an assay with an existing one, it is important to verify the optimal peaks and bandwidths for excitation and emission with spectral scanning in order to obtain the best results.



Fluorescence spectral scan of Alexa 633 using the LVF Monochromators .

#### **Dynamic Luminescence Detection**

Luminescence assays such as flash, glow, dual glow, and BRET are some of the most commonly measured assays on a microplate reader. With the CLARIOstar's high performance luminescence mode and seven log dynamic range, there is no compromise in luminescence assay performance in this multimode microplate reader.

Additionally, the LVF Monochromator or filters can be used for luminescence measurements. The LVF Monochromator with adjustable bandwidths up to 100 nm is sensitive enough to read dual color luminescence signals at concentrations not possible with conventional monochromators.

# Exceptional Performance in FP, TR-FRET, and AlphaScreen®

For fluorescence polarization (FP), time-resolved fluorescence (TRF and TR-FRET), and AlphaScreen® / AlphaLISA® assays, the CLARIOstar uses specialized components that guarantee exceptional performance without compromise in these assays.

#### Fluorescence Polarization

The unique optical design and instant polarizer switching on the CLARIOstar provides the smallest mP standard deviation in fluorescence polarization assays, making the CLARIOstar the world's best FP reader.

#### □ TR-FRET including HTRF®


The CLARIOstar has been certified to measure HTRF® assays in black and white microplates. The ability to use black microplates, which most readers cannot use, guarantees that the CLARIOstar never compromises on any HTRF® assay.

#### AlphaScreen® / AlphaLISA®

A dedicated laser for Alpha Technology and specialized optics ensure the best performance for these assays on the CLARIOstar with respect to speed, assay window, and sensitivity.

# Integrated Fluorophore Library


To greatly simplify and improve assay setup, a library of spectra for the most common fluorophores and lumiphores is integrated into the CLARIOstar's filter visualization tool. Users can measure assays with the recommended settings, or simply "Drag & Drop" new settings for wavelengths and bandwidths.



Filter visualization tool with an integrated fluorophore and lumiphore library makes it easy to choose filters and monochromator settings.

#### Ultra-fast UV/Vis Absorbance Spectra


For ultra-fast, full spectrum absorbance measurements, the CLARIOstar employs a spectrometer. This technology can capture a full UV / Vis absorbance spectrum (220 to 1000 nm) at selectable resolutions (1 to 10 nm) in less than 1 second per well. Fast, full spectrum absorbance will improve all colorimetric assays. Furthermore, users can capture up to eight discrete wavelengths simultaneously in a single measurement with no wavelength switching.



# Focal Height Adjustment

The CLARIOstar incorporates automated focal height adjustment for both top and bottom reading at a resolution of 0.1 mm. The optical system directs the excitation light to a small focal point in the center of the well, giving excellent sensitivity in all plate formats up to 1536 wells.

This feature eliminates the influence of microplate formats, sample volumes, surface tension, and evaporation. The automated focal height adjustment ensures the best signal-to-noise ratio for every plate, every volume, and every application.




Automated focal height adjustment ensures the best signal-to-noise ratio in all detection modes, all plate formats, and all volumes.

# Cell-Based Assays

The CLARIOstar has several key features that improve cell-based applications, including:

 Advanced CeII Layer Scanning allows multiple points to be taken in each well and the software displays each scan point graphically creating a map for each well.
 This feature is perfect for adherent cells that are not distributed evenly in the well.



Well scanning feature for advanced cell-based assays.

- Direct Optic Bottom Reading is an innovative design using lenses and mirrors to direct light to the microplate bottom, thereby significantly improving cell-based assays by eliminating the use of inefficient fiber optics. This feature, along with the LVF Monochromator's adjustable bandwidths, significantly improve fluorescent protein, cell-based assays.
- On-board reagent Injectors deliver precise volumes to stimulate cell-based assays or to initiate kinetic and enzymatic reactions. Delivery volumes are adjustable for each well, allowing users to automatically produce dilution schemes and gradients across the microplate.



On-board reagent injectors deliver precise volumes to initiate kinetic, enzymatic, and cell-based assays.


#### Microplate Stacker and Automation

For medium level throughput, BMG LABTECH offers a Stacker that can be used with the CLARIOstar. The Stacker is an ideal solution for mid-throughput labs that wish to have the small footprint of an automated plate feeder. It provides loading, unloading, restacking, and a continuous load feature for up to 50 microplates.

For higher throughput, the CLARIOstar's small footprint and integrated software allow it to be easily automated with all of the leading robotic platforms.

# Control and MARS Data Analysis Software

BMG LABTECH's well-established Control Software runs the CLARIOstar microplate reader, while data are analyzed with the MARS Data Analysis Software. Both softwares are fully compliant with FDA regulation 21 CFR Part 11 and they can be used on multiple PC systems at no extra cost.



MARS Data Analysis Software for automated data reduction.

The Control Software allows users to easily define instrument parameters and protocols. A new feature in the CLARIOstar is an integrated, upgradable fluorophore library of spectra. With this feature, users can easily and precisely optimize the CLARIOstar for the fluorophore or lumiphore in their assay.

MARS Data Analysis Software allows users to quickly view and analyze data. MARS is able to perform a variety of simple and diverse mathematical calculations. Features include:


- Averaging, blanking, %CVs, and other statistics
- □ Standard curve fits, e.g. linear and segmental regression, 4- and 5-parameter, exponential
- Enzyme kinetics like V<sub>max</sub> or K<sub>m</sub> from Michaelis-Menten, Lineweaver-Burk, or Scatchard Plots
- Predefined templates automatically perform assay-specific calculations
- Equation generator for unique calculations
- □ S:N, S:B, and Z' factor calculations

#### **Applications Center**


A perfectly engineered instrument is only part of the solution, it needs to effectively perform all of the leading applications. With the CLARIOstar, BMG LABTECH offers a sensitive and flexible instrument that supports all existing and future applications, including:

- DNA, RNA, and protein quantification
- □ Cell based assays
- □ Enzyme activity and kinetic assays
- □ Genotyping
- Reporter gene assays
- □ Protein-protein interactions
- Molecular binding assays
- □ And much more ...


Here are a few example applications:



AlphaScreen® P-LCK titration curve using the dedicated Laser.



Transcreener® Fluorescence Polarization (FP) ADP titration curve.



HTRF® cAMP competition titration curve.

BMG LABTECH continuously works with all of the leading reagent companies to optimize settings for their assays.









Visit BMG LABTECH's Applications Center online to find references to all applications, listed as:

- Application notes
- Scientific posters
- □ Peer-reviewed papers

Our comprehensive searchable applications database reflects more than 20 years of expertise and innovations. Over 3,800 published entries of peer-reviewed articles, application notes, and scientific posters demonstrate the flexibility and versatility of our readers, and their use in chemical and biological sciences.

### Support and Training

BMG LABTECH operates globally through an extensive network of subsidiaries and trained distributors. Customers can rely on Ph.D. level support and assistance with regard to software, assay development, or general enquiries related to the CLARIOstar and all other BMG LABTECH microplate reading solutions.

AlphaScreen, AlphaLISA, LANCE and DELFIA are registered trademarks of PerkinElmer, Inc. HTRF is a registered trademark of Cisbio Bioassays LanthaScreen is a registered trademarks of Life Technologies, Corp Transcreener is a registered trademark of Bellbrook Labs DLR is a trademark of Promega Corp.

# Transcreener®

DNA / RNA quantifications

**Protein quantifications** HTRF® Ca2+ assays

Reporter gene assays

Kinase activity

AlphaScreen®/AlphaLISA® **Protease activity** 

LanthaScreen®

S Immunoprecipitation

**Dual luciferase assays** 

BRET assays Apoptosis

ROS detection

Enzyme kinetics

PCR product quantifications

NADH / NADPH assays

ELISA

**Cell Viability** 

ATP and ADP detection

**LANCE®** 

Binding studies

Enzyme activity

Gene expression

Solubility tests

**SNP Genotyping** 

